



RIGID CULTIVATOR

Rigid Cultivator is capable to withstand tough working conditions at heavy soils. With deep positive penetrations it can break up hard soil and uproot stubbles to leave the ground perfectly worked. With the spacing adjustments of tine on the frame it can be used for multiple no. of applications and even for paddy cultivation requiring shallow ploughing



SPECIAL FEATURES

- » Heavy duty channel sturdy frame to withstand heavy loads, bending stresses and strains.
- » Thicker tines to restrain from sudden impact loads.
- » Sharp edged points to give easier and deeper penetrations with effective uprooting of crop residue and cutting of heavy soil clods at any soil conditions.
- » Provision for spacing adjustments between tines to be useful for various soil conditions and various crops.
- » Sharp edged Reversible shovels that gives deeper penetrations at any soil conditions and can be reversed and used on the other side after complete wear of one side.
- » Can be used for uprooting after cutting crops or primary tillage operations before Sowing.

MODELS & SPECIFICATIONS

MODELS	PARTICULARS	LENGTH in mm	WIDTH in mm	HEIGHT in mm.	ASSEMBLED ROW WIDTH in mm.	UNDER FRAME CLEARANCE in mm.	WEIGHT in Kgs.
7 TYNE WITH SHOVELS- HD 7 TYNE WITH DUCK FOOT-HD	FOR 25 HP TO 35 HP TRACTORS	1433	605	1015	210	430	185
9 TYNE WITH SHOVELS- HD 9 TYNE WITH DUCK FOOT-HD	FOR 36 HP TO 50 HP TRACTORS	1843	605	1015	210	430	210

All above specifications are approximate.

As continuous improvements are contemplated, the illustrations and descriptions are not binding. Manufacturers reserve right to discontinue or make change in above models without any prior notice.



SHRI SAI AGRO EQUIPMENTS PVT. LTD.

Plot No. 59 C & D, 1 st Phase, Tarihal Industrial Area, Tarihal, HUBLI- 580026.
State : Karnataka, INDIA.

Phone : +91 - 836 - 2310398, 2310650. Fax : 2310348 Mob : +91 - 99450 59444

Email : info@saiagro.com

Website : www.saiagro.com