SURRY RIDGER

SURRY RIDGER comes with heavy and sturdy mainframe construction to resist heavy bending loads acting during its operation covering wide land area with more surries and ridges. Heavy duty furrows have been provided and inclined at an effective angle such that it can penetrate to greater depths to give deep furrow openings and ridges. Adjustable wingspan enables it to vary furrow as well as width of ridges. Hardened share points uproots residues and obstacles easily and breaking clods effectively. Provision for the adjustment of spacing between the furrows makes it useful forming ridges suit able for various types of crops.



SPECIAL FEATURES

- Longer mainframe to cover wide land area.
- Heavy Duty sturdy mainframe construction.
- Heavy Duty furrows and effective inclination for deeper penetration.
- Adjustable wingspan suitable for varying sizes of surries.
- Provision of adjustment spacing between furrows suitable for various types of crops.
- Hardened sharepoints to uproot residues and break clods easily.

MODELS & SPECIFICATIONS

NO.OF BASES	WIDTH in mm.	LENGTH in mm.	HEIGHT in mm.	UNDERFRAME CLEARANCE in mm.	WINGSPAN ADJUSTMENT in mm.	WEIGHT in Kgs.
2 Nos	1930	435	1175	570	560 to 725	175
3 Nos	2235	435	1175	570	560 to 725	230

All above specifications are approximate.

As continuous improvements are contemplated, the illustrations and descriptions are not binding. Manufacturers reserve right to discontinue or make change in above models without any prior notice.



SHRI SAI AGRO EQUIPMENTS PVT. LTD.

Plot No. 59 C & D, 1 st Phase, Tarihal Industrial Area, Tarihal, HUBLI- 580026.

State: Karnataka, INDIA.

Phone: +91 - 836 - 2310398, 2310650. Fax: 2310348 Mob: +91 - 99450 59444

Email: info@saiagro.com Website: wwww.saiagro.com